



BL021000 Marine FC-W Engine Oil 4-Stroke Outboard EHP 10W-40

Document version: May 13, 2024



Description

This marine FC-W engine oil 4-Stroke outboard EHP has good wear protection under severe conditions and is designed for use in modern 4-stroke water-cooled inboard- and outboard engines. This engine oil meets the latest requirements set by the NMMA. Particularly suitable for use in engines of Mercruiser, Mercury, Suzuki, Honda, Yamaha, Nissan, Johnson/Evinrude, Chrysler Marine etc.

According to the specifications of

API SL
NMMA FC-W (Certificate number: FB-44404M)

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BL021001	1 L	6	450
BL021005	5 L	4	112
BL021020	20 L	1	30
BL021060	60 L	1	6
BL021205	205 L	1	2
BL021999	1000 L	1	-
PBL021000	1 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.88	kg/l
Viscosity	10W-40	
SAE	10W-40	
Kinematic Viscosity at 100°C	14.3	mm ² /s
Viscosity Index	156	
Dynamic Viscosity at -25°C	6300	mPa.s
Flashpoint COC	216	°C
Pourpoint	-30	°C
Total Base Number	7.7	mgKOH/g

These characteristics are typical of current production. Variations in these characteristics may occur.